



SECTIONAL
VALVES

ORV-PD45

CE





CONTENTS

Working Conditions	135
Dimensional Data	136
Hydraulic Circuit	137
Performance Data And Curve	140
Inlet Relief Options	141
Ordering Codes	142
Spool Options	145
Spool Positioners – Side of Return	147
Working Section Kit	151
Spool Positioners – Side of Lever Control	152
Spool Positioners – Side of Lever Control	153
Spool Positioners – Side of Lever Control	154
Spool Positioners – Side of Lever Control	155
Complete Control – On / Off Solenoid Control	156
Outlet Cover- Tank Side	157
Port Valves Options	159
Installation and Maintenance	162
Technical Data	163

Additional Informations

Note: This catalog shows the product in the most standard configurations. For Other Configurations, more detailed information or special request, Please contact Customer Service Dpt.

Warning!: All specifications of this catalog refer to the standard product at this date (01/2020).

ORVAL, oriented to a continuous improvement, reserves the right to discontinue, modify or revise the specifications, without notice.

ORVAL IS NOT RESPONSIBLE FOR ANY DAMAGE CAUSED BY AN INCORRECT USE OF THE PRODUCT.


WORKING CONDITIONS

Nominal Flow Rating / Displacement	45 l/min	12 U.S.G.P.M
Maximum Working Pressure (Series Circuit)	210 Bar	3050 PSI
Maximum Working Pressure (Parallel Circuit)	315 Bar	4600 PSI
Max. Back Pressure	25 Bar	360 PSI
Oil Temperature with NBR Seals	-20 to 80 C°	-4 to 176 F °
with FPM (Viton) Seals	-20 to 100 C°	-4 to 212 F °
Oil Viscosity – Operating Range	From 10 to 75 mm ² /s	From 10 to 75 cSt
Minimum / Maximum	10 / 400 mm ² /s	10 / 400 cSt
Oil Filtration	≤30 μ	
Ambiant Temperature Range	-35 to 60 C°	-31 to 140 F °
Number Of Spools	1 to 12	
Internal Leakage (at 100 bar (1450 PSI), 40C° (110 F°), 46 cSt – A(B)–T)	3 cm ³ /min	0,18 in ³ /min
Max. Level Of Contamination	19/16 – ISO 4406	
Tie rod tightening torque	30 Nm	22 lbft

Not: This catalogue shows technical specifications measured with mineral oil of 46 mm²/s-46 cSt viscosity at 40 C° temperature.

Features

- Simple, compact and heavy duty designed sectional valves from 1 to 12 sections for open and closed center hydraulic systems.
- Optional Carry-Over port only tandem circuit.
- Fitted with a main pressure relief valve.
- Interchangeable spool diameter is 16 mm – 0,63 in.
- Available manual, pneumatic, hydraulic and electro-pneumatic spool control kits.

DIMENSIONAL DATA




TYPE	A		B		Weight	
	mm	in	mm	in	Kg	lb
ORV- PD45-1P	129	5,08	74	2,91	5,9	13,01
ORV- PD45-2P	170	6,69	115	4,53	8,35	18,41
ORV- PD45-3P	211	8,31	156	6,14	10,8	23,81
ORV- PD45-4P	252	9,92	197	7,76	13,25	29,22
ORV- PD45-5P	293	11,54	238	9,37	15,7	34,62
ORV- PD45-6P	334	13,15	279	10,98	18,15	40,02
ORV- PD45-7P	375	14,76	320	12,60	20,6	45,42
ORV- PD45-8P	416	16,38	361	14,21	23,05	50,83
ORV- PD45-9P	457	17,99	402	15,83	25,5	56,23
ORV- PD45-10P	498	19,61	443	17,44	27,95	61,63
ORV- PD45-11P	539	21,22	484	19,06	30,4	67,03
ORV- PD45-12P	580	22,83	525	20,67	32,85	72,43

STANDARD THREADS

PORT	BSP (Iso 228)		UN-UNF (Iso 11926-1)	Metric (Iso 262)
	3/8" Series	1/2" Series		
P Inlet	G 3/8	G 1/2	3/4-16 UNF	M18x1.5
A-B Ports	G 3/8	G 1/2	9/16-18 UNF	M18x1.5
T Outlet	G 1/2	G 1/2	3/4-16 UNF	M18x1.5
Pneumatic	G 1/4	G 1/4	NPTF 1/8 - 27	NPTF 1/8 - 27
Carry-Over	G 1/4	G 1/4	G 1/4	G 1/4

HYDRAULIC CIRCUIT

Parallel




Code: ORV PD45-2P (SD(LA)-SMR2-125-PP)/P-1A-STL-SR/ P-1A-STL-SR/ SO-PT1 / SGT


HYDRAULIC CIRCUIT

Inlet Cover – Pump Side


SD – Side inlet with direct pressure relief valve
TD – Top inlet with direct pressure relief valve



Type = SD




Type = TD




Working Sections

P – Parallel




Type = P




HYDRAULIC CIRCUIT

Outlet Cover (Tank Side)


SO - Side outlet
TO - Top outlet
TCO - Top outlet with carry-over
TC - Top outlet with closed centre




Type = SO





Type = TO



Type = TCO









Type = TC



Valve Type

Production Batch

39.14 = Production Year - Week (2014/39)
101149=Progressive Party Number


PERFORMANCE DATA AND CURVE
Open Center - Pressure Drop (P-T)

Inlet to Work Port - Pressure Drop (P-A/B)

Work Port to Outlet - Pressure Drop (A/B-T)


INLET RELIEF OPTIONS



Direct Pressure Relief Valve

Code:


SMR2 – 125





Performance Data





Adjustment Type on Valve



Relief Blanking Plug - WM



ORDERING CODES
Order Example


ORDERING CODES

1- Inlet Section

ORV PD45-2P PD45 = Valve Type-(PD)- Sectional (45) - Max. Flow Rate
2P = Sections Quantity
SD = Side inlet with direct pressure relief valve (1SD45100)
TD = Top inlet with direct pressure relief valve (1TD45100)

2- Working Section

P = Parallel (2P45100)

3- Output Section

SO = Side outlet (3SO45100)
TO = Top outlet (3TO45100)
TCO = Top outlet with carry-over (3TCO45100)
TC = Top outlet with closed centre (3TC45100)

4- Assembling Kit

Tie rod kit for 1 section valve - (4TRK145100)
Tie rod kit for 2 section valve - (4TRK245100)
Tie rod kit for 3 section valve - (4TRK345100)
Tie rod kit for 4 section valve - (4TRK445100)
Tie rod kit for 5 section valve - (4TRK545100)
Tie rod kit for 6 section valve - (4TRK645100)
Tie rod kit for 7 section valve - (4TRK745100)
Tie rod kit for 8 section valve - (4TRK845100)
Tie rod kit for 9 section valve - (4TRK945100)
Tie rod kit for 10 section valve - (4TRK1045100)
Tie rod kit for 11 section valve - (4TRK1145100)
Tie rod kit for 12 section valve - (4TRK1245100)

5-6- O_Ring Kit

5. -17.00x2.65 NBR 70 SH O-Ring seal (3 Qty.) (5MK45100)
6. -22.40x2.65 NBR 70 SH O-Ring seal (1 Qty.) (6MK45100)

1.*-Inlet Options

1.1 Inlet Cover
Body = Standard (11BS45100)

1.2 Inlet Relief
SMR1-080 - (12SMR145080)-Range 63-125 bar
Setting 80 bar
SMR2-125 - (12SMR245125)-Range 100-160 bar
Setting 125 bar
SMR3-175 - (12SMR345175)-Range 125-250 bar
Setting 175 bar
SMR4-220 - (12SMR445220)-Range 200-315 bar
Setting 220 bar

1.3 Ports Plug
PA1 =G1/2 Top and side input - (13PA045100)
PA2= G1/2 Top and side input -(13PA245100)

2.*- Working Options

2.1 Working Section

PA = Without ports valve prearrangement, with parallel circuit - Body (21BSPA45100)

2.2 Spool Options

1A - (22SS45110) - 3 Positions, Double acting
2A - (22SS45120) - 3 Positions, Double acting
A to tank B Blocked
3A - (22SS45130) - 3 Positions, Double acting
B to tank A blocked
4A - (22SS45140) - 3 Positions, Double acting
A and B tank
5A - (22SS45150) - 3 Positions, Single acting on
A (A to tank)
6A - (22SS45160) - 3 Positions, Single acting on
B (B to tank)

2.3 Lever Options

L =Standard HandLever (L=120mmxM8) - (7L040100)
JL=Joystick lever for two sections operation-(5JL045100)
STL=Standard Lever -(23STL80100)
HL = Remote Cable Kit - (80HL80100)

2.4 Port Relief Valves

Anti-Shock Valve

YAS (T1-50) - (24YAC45050)-Range 35-70 bar
Setting 50 bar
YAS (T1-100) - (24YAC45100)-Range 63-220 bar
Setting 100 bar
YAS (T1-200) - (24YAC45200)-Range 180-350 bar
Setting 200 bar

Anti-Shock and Anti-Cavitation Valve

YAA (T1-63) - (24YAA45063)-Range 35-70 bar
Setting 50 bar
YAA (T1-100) - (24YAA45063)-Range 63-220 bar
Setting 100 bar
YAA (T1-200) - (24YAA45063)-Range 180-350 bar
Setting 200 bar

YAC - Anti Cavitation- (24YAS45100)

YP- A and B ports valve blanking plug (24YP45100)

DST-A and B ports valve blanking plugs with connection to tank-(24DST45100)

2.5 Ports Plug Options

PL1 =Plug for single action spool for 2A-3A, G1/2 (25PL145100)
PL2 =Plug for single action spool for 2A-3A, G3/8 (25PL245100)

2.6 Spool Positioners

SR=Spring Return in neutral position - (26SR45100)
D =Detent in position 1, neutral and 2 -(26D45100)
45P=ON/OFF Pneumatic - (2645P150100)
45EP=12 VDC ON/OFF electro-pneumatic (2645EP150112)
45EH= 12 VDC/24 VDC ON/OFF electro-hydraulic (3645EH100112)

3.*- Working Options

3.1 Working Section

Body = Standard (31BS45100)

3.2 Output Plug

PT1 =G1/2 Top and Side output (32PT145100)

3.3 Circuits Options


CO =G1/8 Carry-Over Connector (33CO45100)

INLET COVER - PUMP SIDE

LH Inlet Valve Options


Type No: **SD**

Sectional Appearance




Type No: **TD**

Sectional Appearance




Hydraulic Diagram

Type No: **SD**









Type No: **TD**





SPOOL OPTIONS

Spool Type - 1A





Performance Curve And Data





SPOOL OPTIONS



Spool Type - 2A





Spool Type - 3A





Spool Type - 4A



Spool Type - 5A



Spool Type - 6A



SPOOL POSITIONERS – SIDE OF RETURN

With Spring Return in Neutral Position

Kit No: **SR**


Sectional Appearance

Allen Wrench 8
24 Nm / 17,7 Ibft

Allen Wrench 5
9,8 Nm / 7,2 Ibft

36,9
[1,45]

Diagram



With Detent

Kit No: **D**

Sectional Appearance

Slotted Wrench 8
24 Nm / 17,7 Ibft


Allen Wrench 5
9,8 Nm / 7,2 Ibft



36,9
[1,45]

Diagram





Force - stroke diagram



SPOOL POSITIONERS – SIDE OF RETURN
ON/OFF Pneumatic Control
Kit No: 45P
Sectional Appearance

Diagram

Operating Features

Pilot Pressure: 6 Bar (Max. 10) / 87 Psi (Max. 145)

ON/OFF Electro-Pneumatic Control
Kit No: 45EP
Sectional Appearance

Diagram

Operating Features

Pilot Pressure: 6 Bar (Max. 10) / 87 Psi (Max. 145)

Solenoid Operating Features

Nominal Voltage.....: 12VDC / 24 VDC



Power Rating.....: 6 W

SPOOL POSITIONERS – SIDE OF RETURN
ON/OFF Electro - Hydraulic Control

 Kit No: **45EH**

Sectional Appearance

Diagram


Operating Features

Pilot Pressure: 10 Bar / 145 Psi
 : 50 Bar / 725 Psi
 Max back pressure on drain L.....: 25 Bar / 360 Psi

Solenoid Operating Features

Coil Connection.....: ISO 4400
 Nominal voltage.....: 12 VDC / 24 VDC
 Power rating.....: 21 W
 Duty cycle.....: %100
 Protection type.....: IP 65
 Nominal voltage tolerance.....: ± 10
 Max temperatures.....: 100 C°
 Stroke.....: $\pm 5,5$ mm

ORDER CODE
External Pilot Collector

COL 11 - 10COL1001 - Kit For Section 1
 COL 12 - 10COL1001 - Kit For Section 2
 COL 13 - 10COL1001 - Kit For Section 3
 COL 14 - 10COL1001 - Kit For Section 4
 COL 15 - 10COL1001 - Kit For Section 5
 COL 16 - 10COL1001 - Kit For Section 6
 COL 17 - 10COL1001 - Kit For Section 7
 COL 18 - 10COL1001 - Kit For Section 8

Standard Pilot Collector


COL 21 - 10COL2001 - Kit For Section 1
 COL 22 - 10COL2001 - Kit For Section 2
 COL 23 - 10COL2001 - Kit For Section 3
 COL 24 - 10COL2001 - Kit For Section 4
 COL 25 - 10COL2001 - Kit For Section 5
 COL 26 - 10COL2001 - Kit For Section 6
 COL 27 - 10COL2001 - Kit For Section 7
 COL 28 - 10COL2001 - Kit For Section 8

SPOOL POSITIONERS – SIDE OF RETURN


ON/OFF Electro - Hydraulic Control Connections

Connection Type 1: Collector kit for external pilot and drain

Sectional Appearance



Diagram




Operating Features

External Pressure Reducing Valve: 20 Bar / 290 Psi (For V line)


Code= ORV PD45-2P (SD(LA)-SMR2-125-PP)/P-1A-STL-45EH/ P-1A-STL-45EH (SMR0 -COL12-12V)/ SO-PT1 / SGT

Connection Type 2: Collector kit with pilot and drain lines

Sectional Appearance



Diagram



SMR 0-25 Valve Operating Features (Pressure reducing valve)

Outlet Pressure: 20 Bar / 290 Psi

Max. Flow.....: 8 l/min

Filtering:80 µ


Code= ORV PD45-2P (SD(LA)-SMR2-125-PP)/P-1A-STL-45EH/ P-1A-STL-45EH (SMR0 -COL22-12V)/ SO-PT1 / SGT

WORKING SECTION KIT


With Port Valves Type

Kit No: **45P**

Sectional Appearance



Diagram





SPOOL POSITIONERS – SIDE OF LEVER CONTROL

Lever Controls

Kit No: **STL - L0**

Sectional Appearance



Diagram



Kit No: **STL - L180**

Sectional Appearance

Diagram



Note: Arm lever pivot box is aluminium cap protected. And it can be rotated 180°.

SPOOL POSITIONERS – SIDE OF LEVER CONTROL

Lever Controls – Joystick

Kit No: **JL**

Exploded View

Diagram

2. section spool

1. section spool

Pivot


Wrench 17 - 42 Nm / 31 lbft

Allen wrench 4 - 6.6 Nm / 4.9 lbft



Wrench 13 - 24 Nm / 17.7 lbft

Wrench 13 - 24 Nm / 17.7 lbft

Allen wrench 6 - 24 Nm / 17.7 lbft





Operation Angle:





SPOOL POSITIONERS – SIDE OF LEVER CONTROL
Lever Controls – Joystick
Dimensions and movement scheme

Type No: **JL1**



Application: Pivot placed down on the Left


Type No: **JL2**



Application: Pivot placed down on the right


Type No: **JL3**

Application: Pivot placed above on the Left


Type No: **JL4**

Application: Pivot placed above on the right



SPOOL POSITIONERS – SIDE OF LEVER CONTROL



Lever Controls – Cable Control

Kit No: **HL**

Sectional Appearance


Diagram

Waterproof cap prearranged for remote control with flexible cable.



Note: Remote cable control has several options. Please indicate the cable length demanded and contact our sales department.

Example Operation





COMPLETE CONTROL – ON / OFF SOLENOID CONTROL
ON/OFF Solenoid Control

 Kit No: **SEC**

Sectional Appearance

Diagram

Electric wiring example


Operating Features

Max Working Pressure.....: 230 Bar / 3300 Psi

Max back pressure: 5 Bar / 80 Psi

 Internal Leakage.....: 10 cm³ / min

Solenoid Operating Features

Nominal voltage.....: 12 VDC / 24 VDC


Power rating.....: 36 W

Duty cycle.....: %100

Nominal voltage tolerance.....: ±10

Coil insulation: Class H

Stroke.....: ±3




OUTLET COVER - TANK SIDE

Output Cover Options


Kit No: **SO**

Sectional Appearance




Kit No: **TO**

Sectional Appearance




Hydraulic Diagram

Type No: **SO**



Type No: **TO**




OUTLET COVER - TANK SIDE

Output Cover Options


Kit No: **TCO**

Sectional Appearance




Kit No: **TC**

Sectional Appearance




Hydraulic Diagram

Type No: **TCO**



Type No: **TC**



PORT VALVES OPTIONS

Anti Shock Valves

Code:

YAS-1 (T1-100)

Pressure Setting in Bar

Adjusting type T=With screw , L=Valve Set / Spring Type (1,2,3)




1 = Mounted Port A , 2 = Mounted Port B , 3 = Mounted Port A and B

Hydraulic Diagram

Kit No: **YAS1**

Kit No: **YAS2**



Kit No: **YAS3**







Adjustment Type on Valve:

T = With screw

L = Valve set



Performance Data:



PORT VALVES OPTIONS

Anti shock And Anti Cavitation Valves

Code:

YAA-1 (T1-100)


Pressure Setting in Bar

Adjusting type T=With screw , L=Valve Set / Spring Type (1,2,3)


1 = Mounted Port A , 2 = Mounted Port B , 3 = Mounted Port A and B

Hydraulic Diagram


Kit No: **YAA1**



Kit No: **YAA2**



Kit No: **YAA3**




Adjustment Type on Valve:

T = With screw


Allen Wrench 24
42 Nm / 31 lbf ft

Allen Wrench 22
42 Nm / 31 lbf ft

Notch
1,5 mm/0,0059 in




L = Valve set




Performance Data:


Spring No=1, Setting 63 bar / 900 psi




Spring No=2, Setting 100 bar / 1450 psi



Spring No=3, Setting 200 bar / 2900 psi



Response time



PORT VALVES OPTIONS

Anti Cavitation Valves

Code:

YAC-1




→ 1= Mounted Port A , 2=Mounted Port B , 3=Mounted Port A and B

Hydraulic Diagram



Kit No: **YAC1**

Kit No: **YAC2**

Kit No: **YAC3**



Adjustment Type on Valve And Data:






Valve Blanking

Plug with tank connection

DST-1 (1:Mounted port A – 2:Mounted port B)





Sectional Appearance

Hydraulic Diagram



Plug


YP-1 (1:Mounted port A – 2:Mounted port B – 3:Mounted port A and B)




INSTALLATION AND MAINTENANCE

The ORV-PD45 valve is assembled and tested as per the technical specification of this catalog. Before the final installation on your equipment, follow the below recommendation:


- The valve can be assembled in any position, in order to prevent body deformation and spool sticking mount the product on a flat surface;
- In order to prevent the possibility of water entering the lever box and spool control kit, do not use high pressure wash down directly on the valve;
- Before painting, ensure plastic port plugs are tightly fitted.




Threads Type (Nm / lbft)	P Port	A and B Port	T Port
BSP (ISO 228/1)	G 3/8	G 3/8	G 1/2
With O--Ring seal	35 / 25.8	35 / 25.8	50 / 36.9
With copper washer	40 / 29.5	40 / 29.5	60 / 44.3
With steel and rubber washer	30 / 22.1	30 / 22.1	60 / 44.3
BSP (ISO 228/1)	G 1/2	G 1/2	G 1/2
With O--Ring seal	50 / 36.9	50 / 36.9	50 / 36.9
With copper washer	60 / 44.3	60 / 44.3	60 / 44.3
With steel and rubber washer	60 / 44.3	60 / 44.3	60 / 44.3
UN--UNF (ISO 11926--1)	3/4--16 UNF--2B	9/16--18 UNF--2B	3/4--16 UNF--2B
With O--Ring seal	50 / 36.9	30 / 22.1	50 / 36.9
METRIC (ISO 262)	M18 x 1.5	M18 x 1.5	M18 x 1.5
With O--Ring seal	35 / 25.8	35 / 25.8	35 / 25.8
With copper washer	40 / 29.5	40 / 29.5	40 / 29.5
With steel and rubber washer	40 / 29.5	40 / 29.5	40 / 29.5

TECHNICAL DATA
Ports Dimensional Data


SAE UN-UNF (ISO 725)							
Dimensions		9/16-18		3/4-16		7/8-14 UNF	
mm	in	UNF SAE6		UNF SAE8		SAE10	
A		13	0,51	15	0,59	17	0,67
B		25	0,83	30	1,18	34	1,34
C		13,6	0,61	20,6	0,81	23,9	0,94
D		2,5	0,10	2,5	0,10	2,5	0,10
E		15°		15°		15°	



BSP (ISO 228)							
Dimensions		G1/4		G3/8		G1/2	
mm	in						
A		14	0,55	14	0,55	16	0,63
B		19	0,75	23	0,91	27	1,06



METRIC (ISO 262)					
Dimensions		M18x1,5		M22x1,5	
mm	in	ISO 262		ISO 262	
A		14	0,55	16	0,63
B		27,5	1.08	31,5	1.24



ORV PD45



ORIGINAL VALVE



Büsan Org. San. Fevzi Çakmak Mah. Kosgeb Cad.
10641. Sk. No: 37 Karatay/KONYA/TÜRKİYE



+90 332 345 29 29



+90 332 345 29 23



satis@orval.com.tr



bilgi@orval.com.tr

